



NOTE:  
 1.TOSLINK TO TOSLINK  
 2.TOSLINK FIBER OPTIC PATCH CABLE  
 OD:4.0mm/BLACK COLOR JACKET  
 3.ONE CABLE ATTACH ONE 3.5mm  
 MINIPLUG ADAPTOR  
 4.USE IN CONSUMER ELECTRONICS PRODUCTS  
 5.PACKAGE MUST ATTENTION AS  
 PICTURE(DETAIL:A)

MAT'L:  
 CHARACTERSITICS OF 2.2mm POF SIMPLEX CABLE  
 1.SCOPE  
 THE TESTING METHODS ARE FOLL OWING JAPAN COMPANY & ALL THE  
 SPECIFICATIONS ARE MET THE INTERNATIONAL STANDARDS.  
 2.OPTICAL ATTENUATION< 0.20dB/m  
 3.MECHANICAL CHARACTERISTICS  
 3.1 TESTIL STRENGTH TEST>8 KG  
 3.2 MINIMUM BENDING RADIUS 35mm  
 4.ENVIROMENTAL CHARACTERISTICS  
 4.1 OPERATING TEMP  
 0°C TO +70°C  
 4.2 STORAGE TEMP  
 -20°C TO +70°C  
 5.QUALITY ASSURANCE  
 ANY INFORMATION ABOUT QUALITY ASSURANCE  
 WILL BE PROVIDED UNDER YOUR REQUEST

6. ITEM NO. & LENGTH:

ITEM NO.	LENGTH
TOTO-1	1000MM
TOTO-2	2000MM
TOTO-3	3000MM

RANGE	0-10	11-25		26-40	41-60	61-80	81-100	X		
TOLERANCE(±)		0.10 0.15	0.20 0.25	0.30 0.35	2%					
TITLE: DEL					Scale	Unit	Rev.	Dwg.no		
TOSLINK FIBER PATCH CABLE					1/1	MM	V1.0	TOTO-X		
DRN BY		CHK BY		APE BY						